

9116LM



SPECIFICATIONS SHEET



- 1. DVR / HVR / NVR features 3-in-1 Encode capacity: 16*720P
- 2. Decode capacity: 1*720P
- 3. Pure analog: 16*720P/8*720P/16*AHD-L
- 4. Purenetwork:1*1080P+
- 5. 8*720P/4*1080P/20*960H
- 6. Analog + network: 4*720P (analog) +4*720P(network) 8*720P (analog) + 8*720P(network)

	Model	9116LM
System	Main processor	Hi3531
	Video compression	H.264(High Profile)
	Encode capacity	16*720P
	Decode capacity	1*720P
Video	Multi-mode input	Pure analog: 16*720P/8*720P/16*AHD-L pure network: 1*1080P+8*720P/4*1080P/20*960H analog + network: 4*720P (analog) + 4*720P(network) 8*720P (analog) + 8*720P(network)
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode Playback	manual>alarm>motion detection>timing 4ch
Storage & backup	Space occupation	Video:~720P 20G / day* channel; 960H 12 ~ 20G / day* channel; Audio: 691.2M / day* channel
	Backup mode	Network, U-disk, USB burner, SATA burner
	Video input	16ch BNC
	Video output	1ch VGA, 1ch HDMI
	Audio input	2ch RCA(Can be expanded to 6ch)
	Audio output	1ch RCA
	Alarm input	O(Can be expanded to 4ch)
Interface	Alarm output Network interface	O(Can be expanded to 1ch) RJ45 10M/100M
	PTZ control	1*RS485, Support multiple PTZ protocols
	USB	2* USB 2.0
	HDD	2*SATA port (Max 4TB/per)
	Wireless	3G, WIFI (extension via USB)
other	Power supply	12V/4A







