

HS-700

LCD Ultra-thin GSM Alarm System







- To realize dial-up alarm and SMS alarm by advanced GSM Technology
- ♦ 99 wireless and 8 wired defense zones.
- Can store 5max. wireless remote controller codes by smart learning
- LCD image&text display, built-in calendar & clock, operate easily
- Full human voice prompt for operation
- SMS instructions remote control Host's arm/disarm, Siren on/off
- SMS prompts of AC power broken and recover, low battery power
- Built-in intercom speaker, can achieve duplex intercom function
- Built-in wireless transmitter module, wireless siren system can be linked and smart home
- ♦ 6 gourps of voice alarm phones (mobile phone), 2 sms alarm mobile recorded
- ♦ 10 seconds message recording playback, 40 alarm events can be
- Remote control: host arm, disarm, monitor, intercom, on/off Siren
- Built-in Lithium rechargeable cell pack, power off alarm

HS-700 Technical Parameter			
Static current	≤66mA	Alarm current	≤650mA
Power adaptor input	AC 100-240V/0.3A, 50/60Hz	adaptor output	DC 12V/1000mA
Siren volume	110dB	Working Temperature	-20°c ∼ +55°C
Built-in battery	Rechargeable lithium cell 7.2V	Humidity	40% ~ 80%RH
Wireless frequency/ IC	315/433MHz 2262/4.7MΩ	GSM	850/900/1800/1900MHz



