

HS-908

LCD PSTN Alarm System



- ◆ 99 wireless and 8 wired defense zones.
- ◆ At most 8 wireless remote controller codes.
- ◆ LCD image&text display, Built-in calendar & clock, operate easily
- ◆ Built-in intercom speaker, can achieve duplex intercom function
- ◆ 6 groups of voice alarm phones (mobile phone), phones in alarm monitor center. and 2 groups of
- ◆ Password Recovery: whether the console is in defense withdrawal, the lost password can be recovered.
- ◆ Line priority alarm: Host can halt the on-going call and switch to alarm
- ◆ Alarm position Programming: Intelligent automatic speech recognition: SOS alarm, fire alarm, gas leak, magnetic contact alarm, hall alarm, window alarm, balcony alarm and perimeter alarm
- ◆ Event Log Query: Console automatically records 45 pieces of all information concerning defense, withdrawal and alarm events.
- ◆ Built-in NI-MH rechargeable battery pack, power off alarm

HS-908 Technical Parameter

Power adaptor input	DC 12V/500mA	Output current	DC 12V 150mA
Static current	≤50mA	Alarm current	≤450mA
Back-up battery	NI-MH AAA DC7.2V	Encode mode	2262 IC /4.7MΩ
Wireless frequency	315/433MHz available	Siren volume	110dB
Temperature range	-20°C-55°C	Humidity range	40%-80%RH