









# HS13-034

## **RFID Standalone Access Control System**



## Introduction

HS13-034 is an access control devices produced by HCS Security Technology Pvt Ltd, which is made with elegant design and professional surface treatment. The device have lock control, alarm, exit button, door sensor. The wiegand-in interface is used to connect external reader to construct master and slave system. Also the device can be used to connect with a control panel as a reader by wiegand-out interface. The operation can be done on the device through LCD display, also can be done on PC software and upload to the device through TCP/IP, RS232/485 communication. The USB-host is used for data download and upload, including user template and record etc. HS13-034 is suitable for house,small office and factory

Copyright 2013, HCS Security Technology Pvt Ltd. All rights reserved.

HCS Security Technology Pvt Ltd may, at any time and without notice, make changes or improvements to the products and services offered and/or cease producing or commercializing them. The HARATI Security logo and trademark are the property of HCS Security Technology Pvt Ltd

#### Features

### Configuration

Sensor

RS232/485

Lock

Converter

Door

TCP/IP

.....

HS13-034

Electric Bell

RS485

USB Key

HUB

Exit Button

- . Tough casing design
- . Elegant fingerprint sensor
- . Easy installation, safe and reliable
- . Simple and convenient operation method
- . ID card standard, Mifare card optional
- . Full door lock control system
- . Wiegand out to connect with control panel
- . Wiegand in to construct master and slave system
- . Audio prompt and LED feedback guide the user to operate

# Specifications / / //

| Model                        | HS13-034   |
|------------------------------|--|
| ID card Capacity             | 30000  |
| Transaction Capacity         | 50000  |
| Communication                | TCP/IP, RS232/485, USB-Host  |
| Access Control Interface for | 3rd party electric lock, door sensor, exit<br>button, alarm, Door Bell |
| Wiegand Signal               | Output&Input   |
| Standard Functions           | Anti-passback, SMS   |
| Optional Functions           | Mifare, HID, Workcode, Webserver                                       |
| Display                      | LCD  |
| Power Supply                 | 12V DC   |
| Operating Temperature        | 0 °C-45°C  |
| Operating Humidity           | 20%-80%  |
| Dimension(L*W*H)mm           | 143x95.5x39.5  |
| Gross Weight                 | 0.8KG  |

Copyright 2013, HCS Security Technology Pvt Ltd. All rights reserved.



HCS Security Technology Pvt Ltd may, at any time and without notice, make changes or improvements to the products and services offered and/or cease producing or commercializing them. The HARATI Security logo and trademark are the property of HCS Security Technology Pvt Ltd