

Fingerprint Access Control + Time Attendance System

HS13-036

Features:

- Fingerprint reader with durable and highly accurate optical sensor
- 1-touch 1-second employee recognition
- Capacity to store 2200 template and 50000 transactions
- No need to enter PINs
- Supports 50 time zones, 5 groups and 10 unlock combinations
- Tamper-proofs switch and alarm outputs
- Request-to-exit and alarm contacts
- Operates stand-alone without a computer
- TCP/IP, serial and Wiegand interfaces
- Real-time 1-touch data export to 3rd party hosted & non-hosted applications
- Audio-Visual indications for acceptance & rejection of valid and invalid fingerprints
- SDK available for OEM customers and software developers



Specifications:

Fingerprint Capacity	2,200 templates
Transaction Capacity	50,000
Hardware Platform	ZEM500
Sensor	Optical Sensor
Algorithm Version	Finger v9.0
Communication	RS232/485, TCP/IP, USB-host
Access Control Interface for	3rd party electric lock, exit button, alarm, Door Bell
Standard Functions	SMS, DLST, Webserver, Workcode, Anti-passback
Optional Functions	ID Mifare, HID, Scheduled-Bell, 9 digit user ID, Self-Service Query, Automatic Status Switch, Soap, printer
Wiegand Signal	= Input & Output
Display	B&W LCD Screen
Power Supply	12V DC
Operating Temperature	0 °C- 45 °C
Operating Humidity	20%-80%
Dimension(W*H*D)mm	100*194*51.5
Gross Weight	0.97kg

Copyright 2013, HCS Security Technology Pvt Ltd. All rights reserved.

HCS Security Technology Pvt Ltd may, at any time and without notice, make changes or improvements to the products and services offered and/or cease producing or commercializing them. The HARATI Security logo and trademark are the property of HCS Security Technology Pvt Ltd

