



HS13-0A: 125KHz Proximity Card Reader with Keypad

Feature:

- 125KHZ Proximity /13.56MHZ MITARE Card Reader or PIN
- Read Range: Up to 10CM(125KHz)/5CM(13.56MHz)
- Output format
- Card: 26/34bit Wiegand (default)
- PIN: 8 bit for PIN output format

- External LED Control
- External Buzzer Control
- Indoor / Outdoor Operation
- Reverse Polarity Protection

Specification:

| iviodei | H313-0A |
|-----------------------|--|
| Read Range | Up to 10CN |
| Reading Time (Card) | ≤300ms |
| Power / Current | DC 6-14V / Max.70mA |
| Input Port | 2ea (External LED Control, External Buzzer Control |
| Card Output Format | 26bit Wiegand (defau <mark>l</mark> t) |
| PIN Output Format | 8 bit |
| LED Indicator | 3 Color LED Indicators |
| Beeper | Yes |
| Operating Temperature | -20° to +65°C |
| Operating Humidity | 10% to 90% relative humidity non-condensing |
| Color | Black |
| Material | ABS+PC with texture |
| Dimension | ช7.อาใบษางง |
| (W x H x T)mm | |
| Weight | 150ç |
| Index of Protection | 1704 |

Copyright 2013, HCS Security Technology Pvt Ltd. All rights reserved.

HCS Security Technology Pvt Ltd may, at any time and without notice, make changes or improvements to the products and services offered and/or cease producing or commercializing them. The HARATI Security logo and trademark are the property of HCS Security Technology Pvt Ltd