

## VG-E12238HR



## **FEATURES**

- > 1/3" CMOS, 800TVL, with IR-Cut filter
- 3.6mm Lens,
- > 24pcs φ5 IR LED, IR Distance 20m,
- Support OSD, Plastic
- DSP + CCD: 3089







Copyright 2014, HCS Security Technology Pvt Ltd. All rights reserved.

HCS Security Technology Pvt Ltd may, at any time and without notice, make changes or improvements to the products and services offered and/or cease producing or commercializing them. The HARATI Security logo and trademark are the property of HCS Security Technology Pvt Ltd



## **SPECIFICATION**

Model no.	VG-E12238HR
Image Sensor	1/3" CMOS
CCD total Pixels	NTSC: 512(H)*492(V) PAL: 512(H)*582(V)
	NTSC: 525 lines, 60 fields/sec
Scanning system	NTSC: 525 lines, 60 fields/sec
	PAL: 625 lines, 50 fields/sec
Sync system	Internal
Minimum Illumination	0.1 Lux/BW0 Lux(IR ON)
S/N Ratio	48dB (AGC OFF)
Resolution	800 TV Lines
White Balance	ATW / AWC Switchable
Gain Control	AGC ON / OFF Switchable
Electronic Shutter	NTSC: 1/60~1/120,000 sec
	PAL: 1/50~1/120,000 sec
B.L.C Function	ON/OFF Switchable
IR LED	24pcs φ5 IR LED
Video Output	Composite 1.0V p-p at 75 ohm
Gamma Correction	0.45
IR Distance	20m
Lens	3.6mm Lens (6mm Lens is optional)
AUTO IRIS	VIDEO / DC
Lens Mount	C/CS / Vail-focal Mount
Operating Temperature	-10°C ~ 50°C
Operational Humidity	Within 85%RH
Color/Material	Black & White / Plastics

Copyright 2014, HCS Security Technology Pvt Ltd. All rights reserved.

HCS Security Technology Pvt Ltd may, at any time and without notice, make changes or improvements to the products and services offered and/or cease producing or commercializing them. The HARATI Security logo and trademark are the property of HCS Security Technology Pvt Ltd

