

VG-E13293HR



FEATURES

- 1/3" Sony, 700TVL,
- 6mm Lens,
- > 24pcs φ5 IR LED, IR Distance 20m,
- Support OSD, Metal housing
- ➤ DSP + CCD: Nextchip 2090+











HCS Security Technology Pvt Ltd may, at any time and without notice, make changes or improvements to the products and services offered and/or cease producing or commercializing them. The HARATI Security logo and trademark are the property of HCS Security Technology Pvt Ltd







SPECIFICATION

VG-E13293HR Model no.

Image Sensor 1/3" Sony CCD Effio-E

CCD total Pixels PAL: 976(H)*582(V) NTSC: 976(H)*494(V)

NTSC: 525 lines, 60 fields/sec

NTSC: 525 lines, 60 fields/sec Scanning system

PAL: 625 lines, 50 fields/sec

Internal Sync system

IP65 Waterproof Level

Minimum Illumination 0.1 Lux/BW0 Lux(IR ON)

S/N Ratio 52dB (AGC OFF)

700 TV Lines Resolution

ATW / AWC Switchable White Balance

AGC ON / OFF Switchable Gain Control

Electronic Shutter NTSC: 1/60~1/120,000 sec

PAL: 1/50~1/120,000 sec

ON/OFF Switchable **B.L.C Function**

IR LED 24pcs φ5 IR LED

Video Output Composite 1.0V p-p at 75 ohm

Gamma Correction 0.45

20m IR Distance

6mm Lens (3.6mm Lens is optional) Lens

-VIDEO / DC **AUTO IRIS**

C/CS / Vail-focal Mount Lens Mount

-10 °C ~ 50°C **Operating Temperature**

Within 85%RH **Operational Humidity**

Black & White / Plastics Color/Material





