



More Capacity and Wireless Connection

Introduction

HS-75-RFC is a face identification T&A terminal with face, PIN and RFID recognition modes. With the latest face identification algorithm and streamlines technology, it can hold 400 face templates without dividing into groups and complete verification in less than 1 second. Communicating via Wi-Fi, Ethernet, and data transfer. All the settings can be easily done on 3 inch TFT touch screen. It has elaborately designed and finely processed to match your slap-up office perfectly.



SPECIFICATIONS

Display	3-inch Touch Screen
Face Capacity	400(1:N)
ID card Capacity	10,000
Logs Capacity	100,000
Communication	Wi-Fi, Ethernet, USB(host and client)
Standard Functions	IDcard, Automatic Status Switch, Self-Service Query, Work Code, T9 Input, 9 Digit User ID, DLST, Scheduled bell and short Message.
Optional function	Mifare Card.
Power supply	12V/1.5A
Verification Speed	<=1S
Operating Temperature	00C-450C
Operating Humidity	20%-80%
Dimensions	104.70(L)*160.00(H)*36.00(W) mm



Download Brochure

HARATI
SECURITY

HCS Security Technology Pvt Ltd

Siddhi Bhawan, Kantipath, Kathmandu, Nepal

Tel: 4260622 Fax: 4267810

info@harati.com.np

www.harati.com.np

Buy Online: www.haratistore.com

FEATURES

- Elegant ergonomic design.
- Wi-Fi, Ethernet, and USB (host and client) communication.
- 3-inch TFT touch screen, T-Input, and 9 Digit User ID.
- Infra-red optical system enables user-identification in poorly lit environment.
- Optional Mifare card module.
- Professional face identification algorithm.

CONFIGURATION

